

FLOOR CARE GUIDE FOR PERMADUR®

HARO®
HARDWOOD FLOOR

HARO®
FURNETT



PERMADUR®
HIGH FINISH



MAINTAINING HARO FLOORING SURFACES WITH PERMADUR® HIGH-FINISH – SIMPLY EASY

You have chosen HARO HARDWOOD FLOOR or HARO FURNETT with PERMADUR® high-finish. The PERMADUR® high-finish is the result of years of research in our in-house laboratories in cooperation with technical institutes. It closes the wood pores in the flooring surface. Dirt and dust no longer stick to the pores and can easily be vacuumed or wiped away.

This ensures a pleasant atmosphere which is very much appreciated, especially by allergy sufferers.

In addition, the superior PERMADUR® high-finish is particularly wear-resistant, scratch-resistant and durable. Your flooring surface will be well-preserved in all its beauty for years and years. Experience has shown, for example, that a hardwood floor sealed with PERMADUR® high-finish lasts about twice as long as a conventional, factory prefinished hardwood floor before the first renovation becomes necessary.

HARO HARDWOOD FLOOR 4000 plank +strip beech steamed Country





(1)



(2)



(3)



(4)

AFTER INSTALLATION

Immediately after laying HARO FURNETT or HARO HARDWOOD FLOOR with PERMADUR® high-finish you should carry out first treatment with HARO Secura-A. HARO Secura-A significantly reduces the absorption of water during damp mopping and protects the seams and surface against moisture, thus preventing a swelling of the board edges.

And here's how it's done:

Remove all dust, dirt and grit from the flooring surface (do not damp mop!). The floor must be completely dry before treatment (1).

Apply HARO Secura-A evenly and as thin as possible using a double-blade spatula. Treat the floor in sections of about 3 sq.m (2), (30 sq.ft). Immediately buff each section after application using a HARO Polishing Cloth (3) or a suitable floor care machine (4) (wrap a HARO Polishing Cloth around the pad!). Never let HARO Secura-A set-up or dry without buffing. Do not walk on buffed areas.

Repeat the above procedure one section at a time to finish the entire flooring surface. It is essential to buff HARO Secura-A until the flooring surface is clear without streaks.

Do not walk on the finished floor for about 8 hours.

Drench used cloths in water or hang up outdoors. Do not fold or crumple up used cloths. Dispose of in a safe way in accordance with local regulations.



HARO HARDWOOD FLOOR 4000 strip Allegro oak ***exquisit



DRY CLEANING

It is usually absolutely sufficient to clean HARO HARDWOOD FLOOR or HARO FURNETT with PERMADUR® high-finish dry using a mop, soft broom or vacuum cleaner. You can damp mop the floor whenever required. For especially effective dry cleaning we recommend our special HARO Easy Clean cleaning cloth.

DAMP CLEANING AND CARE



We recommend damp mopping your HARO flooring surface regularly with HARO Polish. The frequency hereby depends on the wear and tear your floor is subjected to. HARO Polish is a solvent-free polish for regular cleaning and care of your floor.

And here's how it's done:

Add about 200 ml (7 fl.oz.) of HARO Polish to 8–10 litres (2–2.5 gal) of water. Apply the solution evenly to the flooring surface with a well-wrung cloth. Do not make the floor too wet and **never leave puddles.**



HARO

Although buffing with a HARO Polishing Cloth is not required when using HARO Polish, it will further enhance the gloss of your floor.



HARO FURNETT 4000 plank 1-strip canad. maple



INTENSIVE CLEANING

To avoid major soiling of your floor, we strongly recommend regular intensive cleaning with HARO Basic Cleaner. HARO Basic Cleaner is a powerful, solvent-free cleaner for intensive cleaning and for the fast and gentle removal of polish residue or ingrained dirt. In low-traffic areas (e.g. bedrooms) it is usually sufficient to treat your floor with HARO Basic Cleaner once a year, in medium to high-traffic areas (e.g. hallways) twice a year.

And here's how it's done:

Add about 250 ml (8.5 fl.oz.) of HARO Basic Cleaner to 10 litres (2.5 gal) of water. Apply the solution to the flooring surface with a well-wrung cloth. Do not make the floor too wet and **never leave puddles**. Leave for about 5 minutes, then pick up with a cloth wrung out in clear water. Treat the floor with HARO Polish after each basic cleaning (see chapter "Cleaning/care").

INTENSIVE CARE

To ensure a long lifetime of your floor, we recommend – apart from first treatment immediately after laying – to carry out intensive care with HARO Secura-A once a year (as described in the chapter "After installation").






HARO HARDWOOD FLOOR 4000 longstrip beech steamed Terra



(1)



(2)



(3)

USEFUL TIPS

1. Climatic conditions

What is good for people is also good for your HARO floor. A room temperature of 20°C (68°F) at a relative humidity of about 50%–60% is ideal. During the heating season, this relative humidity value is often fallen below to a considerable extent. To prevent the wood from drying out, it is advisable to use an electrical humidifier (1) (available in HARO SHOP), right from the beginning of the heating season.

2. Additional protection for your floor

To preserve the quality and beauty of your floor we recommend using protective pads under chairs and furniture legs (2) (available in HARO Shop). Place quality walk-off mats at entrances, garages and basements to minimise tracked-in dirt, grit and moisture. For additional protection, it is a good idea to place polycarbonate protective mats (3) from HARO Shop under castor-fitted chairs.

MAINTAINING HARO FLOORING SURFACES WITH PERMADUR® HIGH-FINISH

		HARO Easy Clean	HARO Secura-A	HARO Polish	HARO Basic Cleaner	HARO Polishing Cloth	HARO Double-Blade Spatula
							
After installation		–	x	–	–	x	x
Cleaning/ care	Dry cleaning	x	–	–	–	–	–
	Damp cleaning/ care	–	–	x	–	x	–
Intensive cleaning/ care	Intensive cleaning	–	–	–	x	x	–
	Intensive care	–	x	–	–	x	x

If you have any further questions or suggestions, your HARO dealer is always available.

HARO®

QUALITY FLOORING

Hamberger Industriewerke GmbH

P.O.B. 10 03 53 · 83003 Rosenheim · Germany

Telefon +49 (8031) 700-0 · Telefax +49 (8031) 700-600/610

E-Mail mail@hamberger.de · Internet www.haro.com